

High gain target designs for inertial fusion energy

Alison Christopherson and Max Tabak

January 28, 2022

1 Executive summary

Several published inertial fusion power plant studies have stated the need for target designs capable of achieving gains of approximately $100\times$ (where gain = fusion energy output/laser energy delivered) at repetition rates of ~ 16 Hz [1]. Such targets must be inexpensive to fabricate (~ 20 -40 cents per target) and they must withstand the target injection process without compromises to the target's quality. For instance, most high gain target designs require the DT fuel to remain below 20 K even though the chamber wall temperature can be as high as 800 K. Furthermore, achieving significant fuel burnup requires the assembly of a large DT fuel areal density ($\rho R > 3g/cm^2$) at an ignition relevant temperature of ~ 10 keV. In the standard hot spot ignition scheme, such areal densities can only be achieved either by increasing the energy coupled to the fuel (which is often limited by the driver) or by lowering the fuel adiabat (which can be problematic since low adiabat designs are more vulnerable to the target and drive imperfections seeding the growth of hydrodynamic instabilities). To address some of these issues, we propose the following five research questions which could be addressed via the allocation of adequate designer time and computational resources:

1. Target designs utilizing liquid DT instead of solid DT[2, 3] are attractive since they circumvent the need for the costly β layering process[4]. Taking target imperfections and drive asymmetries into account, under what conditions (driver energy, implosion velocity, vapor pressure, and fuel adiabat) can liquid DT foam targets ignite and achieve high gains?

2. Target melt during injection is an issue that could potentially affect the feasibility of imploding directly driven targets in the chamber. Can the use of a radiation shield around the capsule circumvent this problem?

3. Low adiabat inertial fusion designs are sensitive to all perturbation seeds, including the fill tube. Is there a way to redesign the shape of the fill tube to reduce its damaging effect on the implosion?

4. To survive target injection, an indirectly driven target will likely need to be held by a thicker tent than what is fielded on current experiments on the National Ignition Facility. Can a high gain design be achieved with such a tent?

5. Two-sided target illumination could be useful since it would decrease the volume associated with the final optics assembly. More importantly, the target would be consistent with a thick liquid wall reactor concept with a 30 year lifetime and an order-of-magnitude lower induced radioactivity than magnetic fusion chambers. Can a high gain indirect drive design be achieved with two-sided illumination by careful design of the hohlraum?

This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344. This document was prepared as an account of work sponsored by an agency of the United States government. Neither

the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

References

- [1] “An Assessment of the Prospects for Inertial Fusion Energy”. National Academies Press. July 2013. ISBN 978-0-309-27224-7.
- [2] R. E. Olson, M. J. Schmitt, B. M. Haines, et al, “A polar direct drive liquid deuterium-tritium wetted foam target concept for inertial confinement fusion”, *Phys. Plasmas* 28, 122704 (2021).
- [3] V. N. Goncharov, et al, “Novel hot-spot ignition designs for inertial confinement fusion with liquid deuterium-tritium spheres”, *Phys. Rev. Lett*, 125, 065001 (2020).
- [4] A. J. Martin, R. J. Simms, and R. B. Jacobs, “Beta energy driven uniform deuterium-tritium ice layer in reactor-size cryogenic inertial fusion targets,” *J. Vac. Sci. Technol. A* 6, 1885 (1988).